

**JGIX.R1431
Fusible Links**[Page Bottom](#)

Fusible Links[See General Information for Fusible Links](#)**GLOBE TECHNOLOGIES CORP**

R1431

1109 W CEDAR ST
PO BOX 1070
STANDISH, MI 48658 USA

Issue B, in the 135, 165, 212, 280, 360 F temperature ratings; rated for loads 3-20 lbs incl.

Issue D, in the 165, 200 F temperature ratings; rated for loads 1-8 lbs incl.

Issue ML, in the 135, 165, 212, 280, 360, 450, 500 F temperature ratings; rated for loads from 10-40 lbs incl.

Model A, in the 135, 165, 212, 280, 360F, temperature ratings rated for loads 3-45 lbs incl.

Model A, in the 450 F temperature rating, rated for loads of 10-45 lbs. inclusive.

Model CS, in the 135 F temperature rating for loads of 1-4 lbs. incl.

Model EA, in the 135, 155, 165 and 212 °F temperature ratings; rated for loads 5-25 lbs. incl.

Model G, in the 155, 165, 212, 280, 350 F temperature ratings rated for loads 3-45 lbs incl.

Model GS, in the 155, 165, 212, 280, 350 F temperature ratings rated for loads 3-45 lbs incl.

Model J, in the 135, 155, 165, 212, 280 F temperature ratings; rated for loads of 3 to 10 lbs incl.

Model JE, in the 135, 155, 165, 212, 280 F temperature ratings, rated for loads of 3 to 10 lbs incl.

Model JS, in the 135, 155, 165, 212, 280 F temperature ratings, rated for loads of 3 to 10 lbs incl.

Model K, in the 135, 165, 212, 280, 360, 450 F temperature ratings; rated for loads 3-50 lbs. incl.

For use in connection with automatic closing devices for doors, windows, and other automatic devices requiring fusible links.

Trademark and/or Tradename: "AMEREX", "ANSUL"

[Last Updated](#) on 2008-02-20

[Questions?](#)[Print this page](#)[Notice of Disclaimer](#)[Page Top](#)

[Copyright © 2010 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright ©

2010 Underwriters Laboratories Inc.®

An independent organization working for a safer world with integrity, precision and knowledge.

